

**Amendment to the Claim:**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure in the form of a plurality of interconnected, transversely collapsible cells of quadrilateral transverse cross-section, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, wherein movement of said vanes is totally dependant on movement of said support structure.
2. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible cells of quadrilateral transverse cross-section, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes being strips of flexible material, wherein movement of said vanes is totally dependant on movement of said support structure.
3. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible cells, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes being secured to said support structure at two locations where said cells are interconnected.
4. (withdrawn) The fabric of claim 3 wherein said cells are hexagonal in transverse cross-section.
5. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible cells, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes being formed from one continuous sheet of material connected to said cells at spaced locations along said support structure with each vane being defined between adjacent locations where the sheet of material is connected to the cells, wherein movement of said vanes is totally dependant on movement of said support structure.
6. (withdrawn) The fabric of claim 5 wherein said sheet of material is flexible.
7. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible cells, and a plurality of parallel elongated vanes formed from strips of flexible material, said vanes being supported at spaced locations

along said support structure, with each of said cells being formed from the same strip of material as an associated vane and being integral therewith, wherein movement of said vanes is totally dependant on movement of said support structure.

8. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible cells, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, wherein said cells are closed and movement of said vanes is totally dependant on movement of said support structure.

9. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of interconnected, transversely collapsible open cells, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, wherein movement of said vanes is totally dependant on movement of said support structure.

10. (withdrawn) The fabric of claim 9 wherein each of said vanes is secured to a cell.

11. (withdrawn) The fabric of claim 10 wherein said vanes are secured to fewer than all of said cells.

12. (withdrawn) The fabric of claim 10 wherein each of said cells is a strip of semi-rigid material having longitudinal fold lines defining a top wall, a bottom wall, a rear wall with upper and lower segments, said rear wall interconnecting said top and bottom walls and an open front.

13. (withdrawn) The fabric of claim 12 further including a flap along said upper wall partially overlying said front of each cell.

14. (withdrawn) The fabric of claim 13 wherein said slats are secured to said cells along said flap.

15. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a pleated semi-rigid material defining forwardly/downwardly sloped segments and rearwardly/downwardly sloped segments, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, said slats being secured to said forwardly/downwardly sloped segments.

16. (withdrawn) The fabric of claim 15 wherein some of said slats are secured to said rearwardly/downwardly sloped segments.

17. (withdrawn) The fabric of claim 15 or 16 wherein said slats are arcuate in transverse cross-section.

18. (withdrawn) A fabric for use in a covering for a building structure comprising in combination: a flexible vertically extending support structure comprised of a plurality of cord ladders having a pair of riser cords interconnected by vertically spaced rungs, and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, wherein movement of said vanes is totally dependant on movement of said support structure.

19. (withdrawn) The fabric of claim 18 wherein said slats have a pair of spaced holes adjacent to one longitudinal edge thereof, said holes adapted to receive riser cords of a cord ladder such that the slat is supported by a rung adjacent to said spaced holes.

20. (withdrawn) The fabric of claim 19 further including slots in each slat associated with each of said holes, said slots connecting a hole through said one longitudinal edge of said slat to facilitate threading said riser cords through said holes.

21. (cancelled)

22. (withdrawn) The fabric of claim 5 wherein said fabric is vertically disposed.

23. (withdrawn) The fabric of claim 5 wherein said fabric is horizontally disposed.

24. (cancelled)

25. (withdrawn) The fabric of claim 21 wherein said slats have a cross-sectional shape similar to a W turned on its side.

26. (withdrawn) The fabric of claim 21 wherein said slats have a cross-sectional shape similar to a V turned on its side.

27. (cancelled)

28. (withdrawn) The fabric of claim 27 wherein said second fabric comprises a roll-up shade.

29. (withdrawn) The fabric of claim 27 wherein said second fabric comprises a plurality of transversely collapsible interconnected cells.

30. – 34. (cancelled)

35. (currently amended) A The combination of a plurality of adjacent fabrics positioned in one or a plurality of adjacent architectural openings in a building structure, each fabric comprising in combination: a flexible vertically extending support structure and a plurality of parallel elongated vanes supported at spaced locations along said support structure, said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure wherein movement of said vanes is totally dependant on movement of said support structure, each of said fabrics including a top edge and a bottom edge, one of said top and bottom edges being fixed in an associated architectural opening and the other of said edges being non-linear and vertically movable, said other of said edges being alignable and forming a continuation of with the associated other edge of an adjacent fabric so as to form a substantially continuous non-linear edge of the aggregate plurality of fabrics.

36. (cancelled)

37. (previously presented) A covering for an architectural opening comprising the fabrics of claim 35 and a control system for moving said fabrics between extended and retracted positions relative to said architectural opening.

38. (previously presented) The covering of claim 37 wherein said fabrics have upper and lower edges and said control system includes lift cords anchored to said bottom edges for lifting said bottom edges toward said upper edges when retracting said covering.

39. (previously presented) The covering of claim 37 wherein said control system includes cords anchored to said top edges for moving said top edges toward said bottom edges when retracting said covering.

40. (withdrawn) A covering for an architectural opening comprising the fabric of claim 1, 15, 21 or 35, said fabric having an upper edge, and a control system for moving said fabric between extended and retracted positions relative to said architectural opening, said control system including a roller secured to said upper edge around which said fabric can be wrapped when the covering is retracted.

41. (withdrawn) A covering for an architectural opening comprising in combination, a collapsible fabric having an upper and lower edge, vertically extending fixed guide cords disposed in such architectural opening, a movable rail secured to said upper or lower edge of said fabric, the other of said upper and lower edges being fixed in said architectural opening, and wherein said guide cords are slidably and operatively connected to said rail such that said rail can be moved along said guide cords and remain in any selected position relative to said guide cords.

42. (withdrawn) A covering for an architectural opening comprising in combination: a collapsible fabric having an upper edge and a lower edge, vertically extending fixed

guide cords disposed in said architectural opening, upper and lower movable rails secured to said upper and lower edges of said fabric respectively, and wherein said guide cords are slidably and operatively connected to said upper and lower movable rails such that said rails will remain in any selected position relative to said guide cords.

43. (withdrawn) The covering of claim 41 or 42 further including an upper and lower fixed rail to which said guide cords are connected.

44. (withdrawn) The covering of claim 43 wherein said movable and fixed rails are of identical construction.

45. (withdrawn) The covering of claim 41 wherein said other of said upper and lower edges is fixed to one of said upper and lower fixed rails and said upper and lower fixed rails are secured to said architectural opening.

46. (withdrawn) A covering for an architectural opening comprising in combination, a collapsible fabric having an upper and lower edge, vertically extending guide cords suspended in said architectural opening, a weighted bottom rail secured to said lower edge of said fabric, and a movable upper rail secured to said upper edge of said fabric, said upper rail being slidably and operatively connected to said guide cords such that said upper rail can be moved along said guide cords and remain in any selected position relative to said guide cords.

47. (cancelled)

48. (cancelled)

49. (currently amended) A fabric for use in a covering for a building structure comprising in combination:

a plurality of elongated vanes having an elongated flexible component with first and second longitudinal edges and an elongated semi-rigid or rigid component with first and second longitudinal edges, said first edges of said components being connected, said second edge of each flexible component being directly connected to an adjacent vane.

50. (currently amended) The fabric of claim 49 wherein said second edge of each flexible component is directly connected to an adjacent vane at the connection of said first edges of said components of said adjacent vane.

51. (currently amended) A fabric for use in a covering for a building structure movable between an extended position and collapsed retracted position comprising in combination:

- a flexible support structure having an exterior surface; and

- a plurality of parallel elongated vanes ~~supported connected individually and directly to said support structure~~ at spaced locations along said support structure, all said vanes being attached directly to said exterior surface of said support structure and being adapted to move in response to movement of said support structure and project from said exterior surface of said support structure when the fabric is moved between said extended and retracted positions.

52. (withdrawn) The fabric of claim 51, wherein said flexible support structure is comprised of a pleated semi-rigid material defining forwardly/downwardly sloped segments and rearwardly/downwardly sloped segments.

53. (withdrawn) The fabric of claim 52, wherein said vanes comprise semi-rigid slats secured to said support structure so as to form an acute angle with said support structure, said slats being secured to said forwardly/downwardly sloped segments.

54. (withdrawn) The fabric of claim 53, wherein some of said slats are secured to said rearwardly/downwardly sloped segments.

55. (withdrawn) The fabric of claim 53 or 54 wherein said slats are arcuate in transverse cross-section.

56. (withdrawn) The fabric of claim 51 wherein said support structure is comprised of a plurality of interconnected, transversely collapsible cells.

57. (withdrawn) The fabric of claim 56 wherein said transversely collapsible cells are open cells.

58. (withdrawn) The fabric of claim 56 or 57 wherein said cells are hexagonal in transverse cross-section.

59. (withdrawn) The fabric of claim 56 or 57 wherein said vanes are secured to said support structure at two locations where said cells are interconnected.

60. (withdrawn) The fabric of claim 52 or 53, wherein said vanes are formed from one continuous sheet of material connected to said cells at spaced locations along said support structure with each vane being defined between adjacent locations where the sheet of material is connected to the cells.

61. (withdrawn) The fabric of claim 60 wherein said fabric is vertically disposed.

62. (withdrawn) The fabric of claim 60 wherein said fabric is horizontally disposed.

63. (withdrawn) The fabric of claim 60 wherein said sheet of material is flexible.

64. (withdrawn) The fabric of claim 56 or 57, wherein said cells are of quadrilateral transverse cross-section.

65. (withdrawn) The fabric of claim 56, wherein said cells are closed and movement of said vanes is totally dependant on movement of said support structure.

66. (withdrawn) The fabric of claim 51, 52 or 56, wherein said vanes comprise semi-rigid slats secured to said support structure so as to form an acute angle with said support structure.

67. (withdrawn) The fabric of claim 51, wherein said flexible support structure is comprised of a plurality of cord ladders having a pair of riser cords interconnected by vertically spaced rungs.

68. (withdrawn) The fabric of claim 67, wherein said vanes comprising semi-rigid slats secured to said support structure so as to form an acute angle with said support structure.

69. (withdrawn) The fabric of claim 67 wherein said slats have a pair of spaced holes adjacent to one longitudinal edge thereof, said holes adapted to receive riser cords of a cord ladder such that the slat is supported by a rung adjacent to said spaced holes.

70. (withdrawn) The fabric of claim 69 further including slots in each slat associated with each of said holes, said slots connecting a hole through said one longitudinal edge of said slat to facilitate threading said riser cords through said holes.

71. (withdrawn) The fabric of claim 51, wherein said support structure is vertically extending.

72. (withdrawn) The fabric of claim 51, wherein said vanes are strips of flexible material.

73. (withdrawn) The fabric of claim 51, wherein said vanes are supported at spaced locations along said support structure, with each of said cells being formed from the same strip of material as an associated vane and being integral therewith.

74. (withdrawn) The fabric of claim 56 or 57 wherein each of said vanes is secured to a cell.

75. (withdrawn) The fabric of claim 74 wherein said vanes are secured to fewer than all of said cells.

76. (withdrawn) The fabric of claim 74 wherein each of said cells is a strip of semi-rigid material having longitudinal fold lines defining a top wall, a bottom wall, a rear wall with upper and lower segments, said rear wall interconnecting said top and bottom walls and an open front.

77. (withdrawn) The fabric of claim 76 further including a flap along said upper wall partially overlying said front of each cell.

78. (withdrawn) The fabric of claim 77 wherein said slats are secured to said cells along said flap.

79. (withdrawn) The fabric of claim 51 wherein said slats have a cross-sectional shape similar to half a tear drop.

80. (withdrawn) The fabric of claim 51 wherein said slats have a cross-sectional shape similar to a W turned on its side.

81. (withdrawn) The fabric of claim 51 wherein said slats have a cross-sectional shape similar to a V turned on its side.

82. (withdrawn) The fabric of claim 51 further including a second fabric vertically aligned and connected to said first-described fabric.

83. (withdrawn) The fabric of claim 82 wherein said second fabric comprises a roll-up shade.

84. (withdrawn) The fabric of claim 82 wherein said second fabric comprises a plurality of transversely collapsible interconnected cells.

85. (withdrawn) The fabric of claim 82 wherein said fabric is non-quadrangular in its vertical configuration.

86. (withdrawn) The fabric of claim 85 wherein said fabric is triangular in its vertical configuration.

87. (withdrawn) The fabric of claim 85 wherein said fabric is semi-circular in its vertical configuration.

88. (withdrawn) The fabric of claim 87 further including a second fabric of semi-circular configuration and wherein said fabrics are positioned in adjacent but inverted relationship so as to be configured in their vertical configuration and in combination as a circle.

89. (withdrawn) The fabric of claim 51 wherein said support structure is a sheet of flexible material.

90. (withdrawn) The fabric of claim 89 wherein said sheet is comprised of a plurality of interconnected strips of said flexible material.